


# WOOL PADS

- \* Unique steaming and delinting process eliminates pad sling with low fuzzing during use.
- \* Industry leading pad durability proven to outperform in the toughest buffing conditions.



## HEAVY CUTTING

*Fast Cut - 100% Twisted Wool*

10-100 7½" x 1½" Velcro

10-111 7½" x 1½" Bolt-On

10-122 8" x 1½" Double Sided

## LIGHT CUTTING

*Clean Cut - 50% Twisted & 50% Untwisted*

*Blended Proprietary Fibers with Wool*

14-400 7½" x 1½" Velcro

14-422 8" x 1½" Double Sided

## LAMBSWOOL POLISHING

*100% Lambswool Knitted Pad*

24-338 3½" x ¾" no arbor hole    24-649 6½" x ¾" no arbor hole

24-538 5" x ¾" no arbor hole    24-738 7" x ¾" with arbor hole

## SILK POLISHING

*Cool Cut - 100% Untwisted*

*Blended Proprietary Fibers with Wool*

16-600 7½" x 1½" Velcro

16-622 8" x 1½" Double Sided

## ACRYLIC POLISHING

*Soft Cut - 100% Untwisted*

*Acrylic Fibers with Wool*

18-800 7½" x 1½" Velcro

18-822 8" x 1½" Double Sided

## ROTARY BUFFER BACKING PLATE

45-965 - 6½" Soft Edge Urethane 5/8" Threaded Backing Plate

- \* Durable urethane flexible plate has a tapered outside soft edge for safe buffing.
- \* Universal backing plate fits all wool pads 7" and greater as well as 7" through 9" foam pads.

